



1. ELECTRICAL SPECIFICATION

Uncertainty is indicated as \pm (% rdgs + no. of dgt) at $23^\circ\text{C} \pm 5^\circ\text{C}$, con relative humidity <80%HR

DC/AC TRMS VOLTAGE

Range	Resolution	Uncertainty	Overload protection
10 ÷ 660V	1V	$\pm(2\%\text{rdg}+2\text{dgt})$	CAT IV 600 to ground

INSULATION RESISTANCE

Range	Test Voltage	Resolution	Uncertainty (*)
0.01MΩ ÷ 0.19MΩ	$\geq 100\text{V DC}$	$\leq 1\%\text{rdg}$	$\pm(5\%\text{rdg}+7\text{dgt})$
0.20MΩ ÷ 199GΩ			$\pm(5\%\text{rdg}+3\text{dgt}) \text{ if } R_{mis} \leq \frac{\text{Test Voltage}}{5\text{nA}}$
0.20MΩ ÷ 499GΩ			$\pm(20\%\text{rdg}+3\text{dgt}) \text{ if } R_{mis} > \frac{\text{Test Voltage}}{5\text{nA}}$
0.20MΩ ÷ 999GΩ			
0.20MΩ ÷ 1.99TΩ			
0.20MΩ ÷ 4.99TΩ			
0.20MΩ ÷ 9.99TΩ	5000V DC		

(*) Load Capacitance < 1nF

Capacitor charging time (@5kV test voltage): 10s (Capacitance = 2μF)

Capacitor discharging time (from 5kV test voltage): 5s (Capacitance = 2μF)

GENERATED TEST VOLTAGE (compliance to IEC/EN61557-2)

Test mode	Nominal test voltage	Uncertainty
AJUSTABLE	100V,250V,500V,1kV, 2.5kV, 5kV	$-0\%, +10\% +15\text{V}$
	100 ÷ 1kV in steps of 25V	
	1kV ÷ 5kV in steps of 50V	
RAMP	100 ÷ 1kV in steps of 25V	$-0\%, +10\% +15\text{V}$
	1kV ÷ 5kV in steps of 50V	

TEST CURRENT

Test Voltage	Test current
100 ÷ 5000V	$1\text{mA} \leq \text{Test Current} \leq 3\text{mA}$ (**)

(**) Test current automatically controlled.

TEST TIME

Setting Range	Resolution
5s – 99min 59s	1s

CAPACITANCE

Range	Resolution	Resistance Load	Test Voltage (Vn)	Uncertainty
1nF ÷ 999nF	1nF	$\geq 5\text{M}\Omega$	$V_n \leq 5\text{kV}$	$\pm(10\%\text{rdg}+5\text{dgt})$
1.00μF ÷ 5.00μF	0.01μF		$V_n \leq 2.5\text{kV}$	
1nF ÷ 999nF	1nF		$V_n \leq 1\text{kV}$	
1.00μF ÷ 9.99μF	0.01μF	$\geq 5\text{M}\Omega$	$V_n \leq 5\text{kV}$	$\pm(10\%\text{rdg}+5\text{dgt})$
10.0μF ÷ 19.9μF	0.1μF		$V_n \leq 2.5\text{kV}$	
1nF ÷ 999nF	1nF		$V_n \leq 1\text{kV}$	
1.00μF ÷ 9.99μF	0.01μF	$\geq 5\text{M}\Omega$	$V_n \leq 5\text{kV}$	$\pm(10\%\text{rdg}+5\text{dgt})$
10.0μF ÷ 49.9μF	0.1μF		$V_n \leq 2.5\text{kV}$	

Capacitor charge time (OV → 5000V): < 3s x 1μF

Capacitor discharge time (5000V → 25V): < 5s x 1μF



HT7051

Rel.1.02 of 20/09/2018

Professional insulation meter up to 5kVDC

Pag 2 of 3

LEAKAGE CURRENT

Range	Resolution	Uncertainty
1nA ÷ 99.9nA	0.1nA	$\pm(7\% \text{rdg} + 3\text{dgt}) \text{ if } R_{mis} \leq \frac{\text{Test Voltage}}{5nA}$
100nA ÷ 999nA	1nA	
1.00µA ÷ 9.99µA	0.01µA	
10.0µA ÷ 9.99µA	0.1µA	
100µA ÷ 999µA	1µA	
1.00mA ÷ 2.5mA	0.01mA	

P.I (Polarization Index) – D.A.R (Dielectric Absorption Ratio)

Range	Resolution	Uncertainty
0.01 ÷ 9.99	0.01	$\pm(5\% \text{rdg} + 3\text{dgt}) \text{ if } R_{mis} \leq \frac{\text{Test Voltage}}{5nA}$ $\pm(20\% \text{rdg} + 3\text{dgt}) \text{ if } R_{mis} > \frac{\text{Test Voltage}}{5nA}$

(*) Load Capacitance < 1nF



2. GENERAL CHARACTERISTICS

DISPLAY, MEMORY, SERIAL INTERFACE

- Backlight LCD with three simultaneous readings:
Group 1 (main) → Insulation Resistance, Leakage Current, PI, DAR, Capacitance
Group 2 → Test voltage (nominal and generated)
Group 3 → Test Time
- Bargraph: 32 segments
- Low battery indications
- Memory: 700 test
- Communication interface: RS232 optoisolated

POWER SUPPLY:

- Internal battery charger, power supply: 220-240V 50/60Hz, 20VA
- Internal NiMH rechargeable battery
- Protection fuse on power supply: T 200mA/250V, Ir: 1.5kA
- Low battery indication: symbol at display
- Battery life: > 7 hours (@ 5kV) on 100MΩ (test time: 10s, delay between two test: 2s)
- Battery recharging time: approx: 4.3 hours
- Auto Power OFF: after 5min since last operation

ENVIRONMENT:

- Ref. Temperature: 23°C ± 5°C
- Working temperature: 0°C ÷ 40°C
- Maximum relative humidity: <80%RH
- Storage temperature: -10°C ÷ 60°C
- Storage humidity: < 80%RH

MECHANICAL DATA:

- Dimensions (L x W x H): 360 x 310 x 195 mm (14.2" x 12.2" x 7.7")
- Weight: about 3.5kg (about 7.8lb)

GUIDELINES

Instrument's safety	IEC/EN61010-1, IEC/EN61557-1, IEC/EN61557-2
Technical documentation :	IEC/EN61187
Accessories safety :	IEC/EN61010-031
Insulation:	Double insulation
Pollution degree:	2
Mechanical protection:	IP40 (open case), IP53 (closed case)
Over voltage category:	CAT IV 600V to ground, max 600V between inputs
Maximum altitude	max altitude 2000m
Patented certification:	TÜV protocol conformity

This instrument complies with the requirements of the European Low Voltage Directives 2014/35/EU (LVD) and EMC 2014/30/EU

This instrument complies with the requirements of the European 2011/65/EU (RoHS) and with the requirements of the European 2012/19/EU (WEEE)